

CEWELD L-Ag45Sn

TYPE	High silver containing Cadmium free brazing alloy.				
ANWENDUNGEN	Brazing a weight range of different metals in maintenance and repair with excellent strength, Boiler making, Tubing, Cooling equipment etc. Do not use this alloy above working temperatures of 200 °C				
EIGENSCHAFTEN	Most universal silver brazing alloy without Cadmium with extreme low operating temperature and high mechanical properties. Due to the addition of Sn. this alloy will show a bright looking joint and is more capillary then the standard silver brazing Alloys. Flux/Paste: CEWELD Super-Flux				
KLASSIFIKATION	AWS EN ISO	A 5.8: BAg-36 17672: Ag 145			
GEEIGNET FÜR	Steels, Copper, Copper alloys, Stainless steel, Cast Iron, Nickel and Nickel alloys. Also suitable for dissimilar joints between these metals.				
ZULASSUNGEN					
SCHWEISSPOSITIONEN	 PA  PB  PC  PD  PE  PF  PG				
TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)	Cu	Zn	Sn	Ag	
	27	25	2.8	45	
MECHANISCHE GÜTEWERTE	Heat Treatment	R _{P0,2} (MPa)	Rm (MPa)	A5 (%)	Hardness
	As Welded		400		HRc
RÜCKTROCKNUNG	Not required				
MELTING RANGE	640 - 680°C				
GAS ACC. EN ISO 14175					