

CEWELD Ceramic Backing strip U shaped

TYPE Ceramic backing strip with U shaped groove for 1 side welding

APPLICATIONS This ceramic backing strip offer special economic advantages for submerged arc welding and MAG welding with solid wires or metal- cored wires in the downhand position as well for positional MAG welding using rutile cored wires with fast freezing slag.

PROPRIÉTÉS Special economic advantages for submerged arc welding and MAG welding dimensions:

| W (mm) | U1 (mm) | U2 (mm) | h (mm) |
|--------|---------|---------|--------|
| 27 | 12 | 1.2 | 8.5 |
| 30 | 14 | 1.0 | 8.5 |
| 35 | 16 | 1.5 | 8.5 |

CLASSIFICATION

CONVIENT POUR -

AGRÉMENTS

POSITIONS DE SOUDAGE




(%)

PROPRIÉTÉS MÉCANIQUES

ETUVAGE Not required

GAS ACC. EN ISO 14175



CEWELD Ceramic Backing strip U shaped

CERAMIC BACKING STRIP U
SHAPED U12X1,2MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 36 metres per box | 8720663410900 |

CERAMIC BACKING STRIP U
SHAPED U14X1,0MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 24 meters per box | 8720663410924 |

CERAMIC BACKING STRIP U
SHAPED U16X1,5MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 24 meters per box | 8720663410917 |