

CEWELD Ceramic Backing strip Ø shaped

TYPE Ceramic backing Round

APPLICATIONS This ceramic backing strip offer special economic advantages for submerged arc welding and MAG welding with solid wires or metal- cored wires in the downhand position as well for positional MAG welding using rutile cored wires with fast freezing slag.

PROPRIÉTÉS Available in the dimensions:

| Ø (mm) | Longueur (mm) |
|--------|---------------|
| 6 | 600 |
| 8 | 600 |
| 10 | 600 |
| 12 | 600 |
| 15 | 600 |

CLASSIFICATION

CONVIENT POUR one side welding with high currents in shipbuilding, pressure vessel fabrication, machine construction, crane building, tank, and general steel building.

AGRÉMENTS

POSITIONS DE SOUDAGE




(%)

PROPRIÉTÉS MÉCANIQUES

ETUVAGE Not required

GAS ACC. EN ISO 14175



CEWELD Ceramic Backing strip Ø shaped

CERAMIC BACKING STRIP Ø SHAPED Ø 10MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 60 meters per box | 8720663410856 |

CERAMIC BACKING STRIP Ø SHAPED Ø 12MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 48 meters per box | 8720663410863 |

CERAMIC BACKING STRIP Ø SHAPED Ø 15MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 42 meters per box | 8720663410870 |

CERAMIC BACKING STRIP Ø SHAPED Ø 6MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 90 meters per box | 8720663410832 |

CERAMIC BACKING STRIP Ø SHAPED Ø 8MM

| Packaging | KG/unit | EanCode |
|-----------|-------------------|---------------|
| 0,6 | 72 meters per box | 8720663410849 |