



CEWELD SA 309LNb strip

certilas® THE FILLER METAL SPECIALIST

TYPE	Solid stainless steel welding strip										
TOEPASSINGEN	Boilers, vessels, tube cladding, valves etc.										
EIGENSCHAPPEN	Latest generation clean melting quality guarantees optimum metallurgical quality and attractive welder appeal. Combined with our high basic electro slag flux FL 830 ESHC excellent results are obtained in both deposition rate as minimum delution rate due to the higher slag temperature compare to other electro slag fluxes.										
CLASSIFICATIE	AWS A 5.9: EQ309LNb~ EN ISO 14343-A: B 22 12 L Nb W.Nr. 1.4556										
GESCHIKT VOOR	SA 309LNb is developed for cladding applications in case AISI 347 is required in the first layer on mild steel.										
GOEDKEURINGEN	CE										
LASPOSITIONS											
TYPICAL CHEMICAL ANALYSIS OF THE FILLER METAL (%)	C 0.05	Si 0.5	Mn 2	P 0.02	S 0.02	Cr 24	Ni 12.5	Mo 0.5			
MECHANISCHE WAARDEN	Heat Treatment		R _{P0,2} (MPa)	Rm (MPa)	A5 (%)	Hardness					
	As Welded		450	600	>30	HRc					
HERDROGEN	Not required										
GAS ACC. EN ISO 14175											